

# NovoSpeed ALU R



The NovoSpeed **Alu R** is a high-speed exterior door that offers good insulation and burglar resistance.

## Specifications

NovoSpeed	Alu R
max. surface area (W x H)	25 m <sup>2</sup>
max. width (W)	5000 mm
max. height (H)	5000 mm
opening speed	1 m/s
closing speed	0.5 m/s
slat height (visible)	80 mm
slat thickness	20 mm
slat wall thickness	0.75 / 1 mm
slat material	anodised aluminium E6/EV1

## Product Benefits

- class 2 wind resistance (EN 12424) up to a door size of 5 x 5 m.
- frequency control included as standard
- compact size for easy installation
- U-shaped side guides
- supplied in the following colours as standard:

9002

9006

9007

9010

7016

## Cost-effective aluminium roller shutter

### Universal roller shutter door

When speed is not a decisive factor, the Novo Speed **Alu R** is an ideal solution.

Offering the same attractive appearance as the Novo Speed ALU S, this door's opening speed of 1 m/s makes it suitable for universal use in interior and exterior openings. As door panel balancing is not required, the NovoSpeed ALU R is compactly dimensioned with smaller side guides and a less powerful drive. This simplified design approach significantly reduces the cost of the door without affecting reliability. Specific features:

- opening speed of 1 metre per second
- one or multiple viewing slats are optionally available

#### Colours

The door is offered in a standard range of RAL colours and can optionally be painted in any (approximation of a) RAL colour.

Available control units:



T100R



T100R FU



See the Technical Data on page 32 for more information, or download the Product Data Sheet from [www.novoferm.nl](http://www.novoferm.nl)