

NovoSpeed ALU S



The NovoSpeed **Alu S** is a high-speed exterior door that offers good insulation and burglar resistance.

Specifications

NovoSpeed	Alu S
max. surface area (W x H)	36 m ²
max. width (W)	8000 mm
max. height (H)	8000 mm
opening speed	2 m/s
closing speed	0.5 m/s
slat height (visible)	75 mm
slat thickness	20 mm
slat wall thickness	2 mm
slat material	anodised aluminium E6/EV1

Product Benefits

- class 3 wind resistance (EN 12424) up to a door size of 5 x 5 m; above that size, we guarantee a wind resistance of up to 8 Bft at a size of 7 x 7 m
- frequency control included as standard
- door panel weight balanced by springs as standard
- guide columns fitted with inspection doors
- safety light curtain up to a height of 2.5 m included as standard
- supplied in an anodised aluminium finish as standard

New generation

Fast 'all-in-one' exterior roller shutter

The Novo Speed **Alu S** is the best there is where high-speed exterior doors are concerned. This door is well insulated, burglar-resistant and exceptionally fast in comparison to traditional doors. So a combination with a rapid roll door is no longer required. A single door system offers everything required for fast logistics with minimum energy loss and stoppages! Specific features:

- opening speed of 2 metres a second
- special slats that keep the noise level when opening to a minimum in comparison with ordinary roller shutter doors
- one or more viewing slats are optionally available
- mechanical emergency release is optionally available

Colours

The door is offered in a standard range of RAL colours and can optionally be painted in any (approximation of a) RAL colour.

Available control units:

