

NovoSpeed

HEAVY | Indoor



The **Heavy Indoor** is a high-speed, electrically operated rapid roll door, specifically designed for interior openings in industrial and commercial buildings.

Specifications

NovoSpeed	Heavy Indoor
max. surface area (W x H)	36 m ²
max. width (W)	6000 mm
max. height (H)	6000 mm
opening speed	1 m/s
opening speed with frequency control	1.5 m/s
closing speed	1 m/s
closing speed with frequency control	0.5 m/s
door curtain weight	1400 gr/m ²
door curtain thickness	1.2 mm

Product Benefits

- class 0 wind resistance
- safety photocell in the door opening
- completely transparent 'Full Vision' door curtain optional

1003

2009

3020

5005

7038

9003

9004

A tower of strength

Workhorse for large openings

The NovoSpeed **Heavy Indoor** has been specially developed for large interior openings up to 36 m². All structural components and the curtain are robustly designed and engineered. Overpressure and underpressure can exert considerable forces on the door curtain. With its 1.2 mm thick door curtain and strong aluminium stiffener/hinge profiles, the **Heavy** is capable of withstanding wind loads of up to 5 Beaufort (28 - 38 km/h). Specific features:

- extra strong, fabricated steel side columns with brushes to seal and guide the door curtain
- a bottom beam with a self-testing bottom safety edge and cast aluminium end pieces of as standard
- the aluminium lower beam is available with a 'break away' crash-protection system, which prevents damage in a collision and allows the door curtain to be repositioned in the guides without having to use special tools

Available control units:



T100R FU

T100R FU 3 kW



See the Technical Data on page 32 for more information, or download the Product Data Sheet from www.novoferm.nl